

| Item No. | Item Description | Specification | Total Cost in Rs. Per item |
|----------|-------------------------|---|----------------------------|
| 1 | 2MP Vandal Dome IR | Res: 25fps@2MP H.265+ ; Lens:3.6 mm fixed lens (2.8 mm optional); IR: 30m; WDR: D-WDR; IP Rating: IP67 | 5623.29 |
| 2 | 2MP Dome IR | Res: 25fps@2MP H.265+ ; Lens:2.8-12mm Motorized lens; IR: 30m; WDR: D-WDR; IP Rating: IP67; SD Card: Yes | 8497.42 |
| 3 | 2MP Bullet IR-40 | Res: 25fps@2MP H.265+ ; Lens:2.8-12mm Motorized lens; IR:40m; WDR: D-WDR; IP Rating: IP67; SD Card: Yes | 8747.34 |
| 4 | 2MP Bullet IR-50 | Res: 25fps@2MP ; Lens:6mm/8mm; IR: 50m; WDR: D-WDR; IP Rating: IP67 | 5873.21 |
| 5 | 2MP Bullet IR-80 | Res: 25fps@2MP ; Lens:6mm/8mm; IR: 80m; WDR: D-WDR; IP Rating: IP67 | 6248.10 |
| 6 | 2MP Dome IR Fixed | Res: 2MP (1920 x 1080) ; Lens:3.6 mm fixed lens ; Image Sensor: 1/2.7" Progressive Scan CMOS; IR range: 20m; WDR: D-WDR; Digital Noise reduction:2D; IP Rating: IP66; Power consumption:<5W; Housing: Plastic | 5060.96 |
| 7 | 2MP Bullet IR Fixed | Res: 2MP (1920 x 1080) ; Lens:3.6 mm fixed lens ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 30m; WDR: D-WDR; Digital Noise reduction:3D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 5498.33 |
| 8 | 2MP Dome IR Varifocal | Res: 2MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 40m; WDR: D-WDR; Digital Noise reduction:2D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 8622.38 |
| 9 | 2MP Bullet IR Varifocal | Res: 2MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 50m; WDR: D-WDR; Digital Noise reduction:3D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 12558.68 |
| 10 | 2MP Dome IR Fixed 6mm | Res: 2MP (1920 x 1080) ; Lens:6 mm fixed lens ; Image Sensor: 1/2.7" Progressive Scan CMOS; IR range: 20m; WDR: D-WDR; Digital Noise reduction:2D; Power consumption:<5W; Housing: Plastic | 7872.61 |
| 11 | 2MP Bullet IR Fixed 6mm | Res: 2MP (1920 x 1080) ; Lens:6 mm fixed lens ; Image Sensor: 1/2.7" Progressive Scan CMOS; IR range: 30m; WDR: D-WDR; Digital Noise reduction:3D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 5810.73 |

| | | | |
|----|--|---|----------|
| 12 | 2MP 4G WiFi Bullet camera | 2.0 MP Outdoor camera IP66 designed ,Two way voice intercom ,Any 4G SIM card supported ,Only Mobile App control and customize alarm audio, Star light night monitoring for superb clarity ,128 GB Micro SD card supported for storage Cloud based storage | 17657.13 |
| 13 | ANPR Camera | Darkfighter Ultra-low light technology• 1920x1080 high resolution• Full HD1080p video, up to 60fps• 120dB WDR• 2.8~12mm Motorized VF lens Smart Auto Focus• Up to 50m IR range• IP67 Weather-proof protection• DC12V & PoE• Support on-board storage, up to 128GB• On-board ANPR Analytics, B/W list filtering• Built-in Smart Heater (-H)• Audio/Alarm IO connectors (-S)• Support Barrier linkage via RS485 | 86848.59 |
| 14 | 2MP Panovu LightFighter 140dB WDR Network Camera | <ul style="list-style-type: none"> • Up to 2 Megapixel high resolution • Full HD1080p, up to 60fps • Up to 30m IR • Full Smart feature-set • 140dB WDR with Triple Exposure • 2.8~12mm Motorized VF lens • Smart Auto Focus • Audio/Alarm IO • Support on-board storage, up to 128GB • UP to 30m IR range • IK10 vandal-proof housing • DC12V, PoE power supply | 49359.99 |
| 15 | 2MP LightFighter 140dB WDR Network Camera | <ul style="list-style-type: none"> Up to 2 Megapixel high resolution • Full HD1080p, up to 60fps • Up to 30m IR • Full Smart feature-set • 140dB WDR with Triple Exposure • 2.8~12mm Motorized VF lens • Smart Auto Focus • Audio/Alarm IO • Support on-board storage, up to 128GB • UP to 30m IR range • IK10 vandal-proof housing • DC12V, PoE power supply | 49359.99 |

| | | | |
|----|-----------------------|---|----------|
| 16 | Face Detection camera | <ul style="list-style-type: none"> 1/1.8" progressive scan CMOS • Full HD1080p video, up to 60fps • 2.8 to 12 mm and 8 to 32 mm motor-driven lens optional • 140dB WDR • Alarm I/O • Color: 0.002 Lux @(F1.2, ADC On) • H.265, H.265+. H.264, H.264+ • IR range: up to 50 m for 2.8 to 12 mm lens and up to 100 m for 8 to 32 mm lens • IP67, IK10 • High accuracy face detection and capture, which adopts new face detection, tracking and grading algorithms powered by deep-learning technology • Perimeter protection, based on deep learning powered target detection and classification algorithms, supports line crossing, intrusion, region entrance, and region exit • Five defined streams and up to five custom streams • Built-in microSD/SDHC/SDXC card slot, up to 256 GB | 83724.54 |
| 17 | Bullet-BLC | <ul style="list-style-type: none"> <input type="checkbox"/> 1/2.8" Progressive Scan CMOS <input type="checkbox"/> 1920 × 1080 @30fps <input type="checkbox"/> 2.8/4/6 mm fixed lens <input type="checkbox"/> Wi-Fi Connection (Optional) <input type="checkbox"/> H.265+, H.265, H.264+, H.264 <input type="checkbox"/> BLC/3D DNR/HLC <input type="checkbox"/> Region of Interest <input type="checkbox"/> 120 dB WDR <input type="checkbox"/> IP67 | 11184.10 |
| 18 | Dome-BLC | <ul style="list-style-type: none"> <input type="checkbox"/> 1/2.8" Progressive Scan CMOS <input type="checkbox"/> 1920 × 1080@30fps <input type="checkbox"/> 2.8/4/6 mm fixed lens <input type="checkbox"/> Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @(F2.0, AGC ON); <input type="checkbox"/> H.265+, H.265, H.264+, H.264 <input type="checkbox"/> 120 dB WDR <input type="checkbox"/> 2 Behavior analyses <input type="checkbox"/> BLC/3D DNR/ROI/HLC <input type="checkbox"/> Built-in micro SD/micro SDHC/micro SDXC card slot, up to 128 GB | 11496.50 |

| | | | |
|----|-----------------------------------|--|-----------|
| 19 | People Counting Camera | <input type="checkbox"/> 1/3" Progressive Scan CMOS <input type="checkbox"/> Dual lens, dual CPU, support stereo views <input type="checkbox"/> 2 mm/2.8 mm/4 mm lens, optional <input type="checkbox"/> Max. resolution 640 × 960 <input type="checkbox"/> H.264 <input type="checkbox"/> Flash memory storing people counting data <input type="checkbox"/> 3D digital noise reduction <input type="checkbox"/> 12 VDC/PoE <input type="checkbox"/> Up to 5 m IR range <input type="checkbox"/> IP66 | 33739.74 |
| 20 | Thermal Camera | <ul style="list-style-type: none"> • 160 × 120 (the resolution of output image is 320 × 240) resolution sensor, high sensitivity sensor, support contrast adjustment • Shutter adjustment in various modes • 3D DNR, 15 palettes of color adjustable, image detail enhancement • Mirror image, digital zoom ×2, ×4, ×8, and local output • Leading image processing technology: Adaptive AGC, DDE, 3D DNR, NETD less than 40 mk (@25°C,F#=1.1) • Powerful behavior analysis function, based on deep learning algorithm: Line crossing, Intrusion, Region Entrance & Exit • Reliable temperature exception alarm function • Advanced fire detection algorithm • Bi-spectrum image fusion, picture in picture preview | 123712.38 |
| 21 | 32x PTZ Camera | 2MP 32X Network IR PTZ Camera <ul style="list-style-type: none"> o 1/2.8" progressive scan CMOS o Up to 1920 × 1080@60fps resolution o Min. illumination: <ul style="list-style-type: none"> Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) o 0 Lux with IR o 32× optical zoom, 16× digital zoom o WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus o Up to 150 m IR distance o 24 VAC & Hi-PoE o Support H.265+/H.265 video compression | 56232.90 |
| 22 | 2MP Speed Domes/PTZ IP Camera-100 | Res: 25/30fps@1080P POE+ 4 Inchs Dome h.265; IR:100 Mtrs.; Zoom:25x; Audio:Yes ,WDR, IP Rating:IP66 | 31240.50 |

| | | | |
|----|-----------------------------------|---|----------|
| 23 | 2MP Speed Domes/PTZ IP Camera-150 | Res: 50/60fps@2MP PoE+ 5 Inchs Dome; IR:150 Mtrs.; Zoom:25x; Audio:Yes ,WDR, IP Rating:IP66 | 37488.60 |
| 24 | 2MP Speed Domes/PTZ IP Camera-200 | Res: 50/60fps@2MP PoE+ 6 Inchs Dome H.265; IR:200 Mtrs.; Zoom:25x; Audio:Yes ,WDR, IP Rating:IP67 | 43736.70 |
| 25 | 2MP Speed Domes/PTZ IP Camera-30x | Res: 50/60fps@2MP PoE+ 6 Inchs Dome H.265; IR:200 Mtrs.; Zoom:30x; Audio:Yes ,WDR, IP Rating:IP67 | 51234.42 |
| 26 | 3MP Speed Dome/PTZ IP Camera-100 | Image Sensor: 1 /2.8"progressive Scan CMOS Sensor; Res:2048(H) ×1536(V)/25 FPS; POE+; H.264; IR:100 Mtrs.; Zoom:12x optical zoom, 16x digital zoom; WDR, IP Rating:IP66; Micro SD support up to 64GB; Housing: Metal | 26491.94 |
| 27 | 3MP Speed Dome/PTZ IP Camera-150 | Image Sensor: 1 /2.8"progressive Scan CMOS Sensor; Res:2048 X 1536 @25fps support 1-25fps; POE+; H.264; IR:150 Mtrs.; Zoom:30x optical zoom, 16x digital zoom; WDR, IP Rating:IP66; Micro SD support up to 64GB; Housing: Metal | 72477.96 |
| 28 | 4MP Dome IR | Res: 20fps@4MP H.265+ ; Lens:3.6 mm fixed lens (2.8 mm optional); IR: 30m; WDR: D-WDR; IP Rating: IP67 | 6435.54 |
| 29 | 4MP Bullet IR | Res: 20fps@4MP H.265+ ; Lens:3.6 mm fixed lens (2.8 mm optional); IR: 30m; WDR: D-WDR; IP Rating: IP67 | 5623.29 |
| 30 | 4MP Vandal Dome IR | Res: 20fps@4MP H.265+ ; Lens:3.6 mm fixed lens (2.8 mm optional); IR: 30m; WDR: D-WDR; IP Rating: IP67 | 7310.28 |
| 31 | 4MP Dome IR | Res: 25fps@2MP H.265+ ; Lens:2.8-12mm Motorized lens; IR: 30m; WDR: D-WDR; IP Rating: IP67; SD card: Yes | 10709.24 |
| 32 | 4MP Dome IR Varifocal | Res: 4MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 40m; WDR: D-WDR; Digital Noise reduction:2D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 13745.82 |
| 33 | 4MP Bullet IR Varifocal | Res: 4MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 50m; WDR: D-WDR; Digital Noise reduction:3D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 13745.82 |
| 34 | 4MP Bullet IR-40m | Res: 25fps@4MP H.265+ ; Lens:2.8-12mm Motorized lens; IR: 40m; WDR: D-WDR; IP Rating: IP67; SD card:Yes | 11184.10 |

| | | | |
|----|-------------------------------|--|----------|
| 35 | 4/5MP Speed Domes/PTZ | Res: 25/30fps@4M 50/60fps@1080P H.265; IR:100 Mtrs.; Zoom:30x; Audio:Yes ,WDR, IP Rating:IP66 | 75227.12 |
| 36 | 5MP Dome IR | Res: 20fps@5MP ; Lens:3.6 mm fixed lens (2.8 mm optional); IR: 30m; WDR: D-WDR; IP Rating: IP67 | 9184.71 |
| 37 | 5MP Vandal Dome IR | Res: 20fps@5MP ; Lens:3.6 mm fixed lens (2.8 mm optional); IR: 30m; WDR: D-WDR; IP Rating: IP67, IK10 | 10246.88 |
| 38 | 5MP Dome IR Fixed (Indoor) | Res: 5MP@20fps; H.265+; Image Sensor: 1/2.5" Progressive Scan CMOS; Lens:3.6 mm fixed lens ; IR: 20m; WDR: D-WDR; 2D/3D DNR; Housing: Plastic | 9184.71 |
| 39 | 5MP Bullet IR Fixed (Outdoor) | Res: 5MP@20fps; H.265+; Image Sensor: 1/2.5" Progressive Scan CMOS; Lens:3.6 mm fixed lens; IR: 20m; WDR: D-WDR; 2D/3D DNR; IP Rating: IP66; Housing: Plastic | 9747.04 |
| 40 | 5MP Bullet IR Fixed (Metal) | Res: 5MP@20fps; H.265+; Image Sensor: 1/2.5" Progressive Scan CMOS; Lens:3.6 mm fixed lens; IR: 30m; WDR: D-WDR; 2D/3D DNR; IP Rating: IP66; Housing: Metal | 9747.04 |
| 41 | 5MP Dome IR Varifocal | Res: 5MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 40m; WDR: D-WDR; Digital Noise reduction:2D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 17557.16 |
| 42 | 5MP Bullet IR Varifocal | Res: 5MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 50m; WDR: D-WDR; Digital Noise reduction:3D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 17557.16 |
| 43 | 8MP Bullet IR | Res: 25fps@8MP ; Lens:2.8mm fixed lens (4mm, 6mm optional); IR: 50m; WDR: D-WDR; IP Rating: IP67 | 12558.68 |
| 44 | 8MP Vandal | Res: 25fps@8MP ; Lens: 4mm fixed lens (6mm optional); IR: 30m; WDR: D-WDR; IP Rating: IP67, IK10;SD Card :Yes | 12527.44 |
| 45 | 8MP Bullet IR-25 | Res: 20fps@8MP; Image Sensor: 1/2.3" Progressive Scan CMOS; Lens:3.6mm fixed lens; IR: 25m; WDR: D-WDR; 2D/3D DNR; IP Rating: IP66; Housing: Metal | 12808.61 |
| 46 | 8MP Dome IR | Res: 20fps@8MP; Image Sensor: 1/2.3" Progressive Scan CMOS; Lens: 3.6mm fixed lens; IR: 25m; WDR: D-WDR; 2D/3D DNR; IP Rating: IP66; Housing: Metal | 12808.61 |
| 47 | Highend Speed Domes/PTZ | Res: 25fps@2MP PoE+; IR:250 Mtrs.; Zoom:45x; Audio:Yes ,WDR, IP Rating:IP67 | 56232.90 |

| | | | |
|----|-------------------------------|--|----------|
| 48 | 2.4 MP HD IR Dome | Res: 2.4 MP; Lens:3.6mm; IR:20M | 1437.06 |
| 49 | 2.4 MP HD IR Bullet | Res: 2.4 MP; Lens:3.6mm; IR:20M | 1686.99 |
| 50 | 2.4 MP HD Dome IR | Res: 1080p/2.4MP; Lens:6mm; IR:30M | 1999.39 |
| 51 | 2.4 MP HD Dome IR | Res: 1080p/2.4MP; Lens: 3.6mm; IR: 50M | 3061.57 |
| 52 | 2.4 MP HD Vandal Dome | Res: 1080p/2.4MP; Lens: 2.7-13.5mm vari-focal lens ; IR: 30M | 4417.41 |
| 53 | 2.4 MP HD Dome IR | Res: 1080p/2.4MP; Lens:3.6mm (2.8mm, 6mm Optional); IR:40M | 4444.90 |
| 54 | 2.4 MP HD Bullet IR-80 | Res: 1080p/2.4MP; Lens:6mm; IR:80M | 4486.14 |
| 55 | 2.4 MP HD Bullet IR-60 | Res: 1080p/2.4MP; Lens:2.7-13.5mm vari-focal lens ; IR: 60M | 4717.32 |
| 56 | 2.4 MP HD Dome IR-30 | Res: 1080p/2.4MP; Lens:3.6mm; IR:30M | 1811.95 |
| 57 | 2.4 MP HD Bullet IR-50 | Res: 1080p/2.4MP; Lens:6mm; IR:50M | 1749.47 |
| 58 | 2.4 MP HD Bullet IR-80 | Res: 1080p/2.4MP; Lens:8mm; IR:80M | 6060.66 |
| 59 | 2.4 MP HD Bullet IR-60m | Res: 1080p/2.4MP; Lens:2.7~13.5mm Motorized; IR:60M | 4611.10 |
| 60 | Full HD Body Worn Camera | 1080P Full HD Recording and Streaming,2.0 inch touch screen supported, Support built-in 4G for live video transmission, Support built-in Wi-Fi, Support built-in GPS for live tracking, Support two-way audio communication ,IP67, Replaceable lithium battery,Built-in battery for hot-swappable function | 44174.07 |
| 61 | 2 MP Full HD Body Worn Camera | Support 1080P HD recording, Support audio recording and snapshot, Support 110 degree wide angle, Support night vision and white light, Support external Camera, Support 16GB~128GB SD card capacity optional | 44174.07 |
| 62 | 3MP Full HD Body Worn Camera | Supports 2304 x 1296P HD recording, Supports 32MP Capture, Support 140 degree wide angle, Support night vision and motion detection, Support external Camera, Support built-in GPS for history tracking, Drop-resistance 2 meters, Support video tagging function | 37801.01 |
| 63 | 4MP HD Dome IR-20 | Res: 4 MP; Lens:3.6mm; IR:20M | 2561.72 |
| 64 | 4MP HD Dome IR-30 | Res: 4 MP; Lens:6mm; IR:30M | 2749.16 |
| 65 | 4MP HD Dome IR | Res: 4 MP; Lens:3.6mm; IR:50M | 10006.96 |
| 66 | 4MP HD Vandal Dome IR | Res: 4 MP; Lens:2.7~13.5mm; IR:30M | 6810.43 |
| 67 | 4MP HD Metal | Res: 4 MP; Lens:3.6mm; IR:20M | 3061.57 |
| 68 | 4MP HD Bullet IR-60 | Res: 4 MP; Lens:2.7~13.5mm; IR:60M | 9059.75 |
| 69 | 4MP HD Dome IR Varifocal | Res: 4MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 40m; WDR: D-WDR; Digital Noise reduction:2D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 7185.32 |

| | | | |
|----|----------------------------|--|----------|
| 70 | 4MP HD Bullet IR Varifocal | Res: 4MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 50m; WDR: D-WDR; Digital Noise reduction:3D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 6935.39 |
| 71 | 5MP HD Dome IR-20 | Res: 5 MP; Lens:3.6mm; IR:20M | 2561.72 |
| 72 | 5MP HD Metal | Res: 5 MP; Lens:3.6mm; IR:20M | 2811.65 |
| 73 | 5MP HD Vandal Dome IR | Res: 5 MP; Lens:2.7~13.5mm; IR:60M | 10621.77 |
| 74 | 5MP HD Bullet IR-30 | Res: 5 MP; Lens:3.6mm; IR:30M | 3061.57 |
| 75 | 5MP HD Bullet IR-50 | Res: 5 MP; Lens:6mm; IR:50M | 3237.77 |
| 76 | 5MP HD Dome IR Varifocal | Res: 5MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 40m; WDR: D-WDR; Digital Noise reduction:2D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 5310.89 |
| 77 | 5MP HD Bullet IR Varifocal | Res: 5MP (1920 x 1080) ; Lens:2.8-12mm varifocal ; Image Sensor: 1/2.9" Progressive Scan CMOS; IR range: 50m; WDR: D-WDR; Digital Noise reduction:3D; IP Rating: IP66; Power consumption:<5W; Housing: Metal | 5560.81 |
| 78 | 5MP HD Bullet IR-60 | Res: 5 MP; Lens:2.7~13.5mm; IR:60M | 10246.88 |
| 79 | HD DVR 4 Channel-1 | Channel: 4CH; Compression & MP: H.264 & 1MP/2MP : Resolution:1080N@25/30fps, 720P@25/30fps, Sata Support: 1, Audio:1, Casing:METAL SMALL | 3748.86 |
| 80 | HD DVR 4 Channel-2 | Channel: 4CH; Compression & MP: H.265 & 2MP/4MP/5MP : Resolution:720P@25fps 1080P@15fps 4M-N@15fps 5M-N@10fps , Sata Support: 1, Audio:1, Casing:METAL SMALL | 5707.01 |
| 81 | HD DVR 8 Channel-1 | Channel: 8 CH; Compression & MP: H.265 & 2MP/4MP/5MP : Resolution:720P@25fps 1080P@15fps 4M-N@15fps 5M-N@10fps , Sata Support: 1, Audio:1, Casing:METAL SMALL | 8122.53 |
| 82 | HD DVR 8 Channel-2 | Channel: 8 CH; Compression & MP: H.265 & 4MP/5MP/4K : Resolution:4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 3MP@15fps, 30fps@4M-N,2MP@30fps , Sata Support: 1, Audio:1, Casing:METAL BIG | 13121.01 |
| 83 | HD DVR 16 Channel-1 | Channel: 16 CH; Compression & MP: H.265 & 4MP/5MP/4K : Resolution:4K@7fps, 6MP@10fps, 5MP@ 12fps, 4MP@15fps, 3MP@15fps, 30fps@4M-N,2MP@30fps , Sata Support: 1, Audio:1, Casing:METAL BIG | 13121.01 |

| | | | |
|----|---------------------|---|----------|
| 84 | HD DVR 32 Channel-1 | Channel: 32 CH; Compression & MP: H.265 & 1MP/2MP : Resolution:720P@15fps 1080N@15fps , Sata Support: 2, Audio:1, Casing:METAL BIG | 28116.45 |
| 85 | HD DVR 4 Channel-3 | Channel: 4CH; Compression & MP: H.264/H.264+ & 1MP/2MP : Resolution:1080N@25/30fps, 720P@25/30fps, HDD: 1 Sata upto 8TB, Audio:1Ch; Upto 6CH IPC @2MP; 1 x HDMI & VGA; 1 x 10/100 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage, 2 x USB. | 3623.90 |
| 86 | HD DVR 4 Channel-4 | Channel: 4CH; Compression & MP: H.264/H.264+/H.265/H.265+ & 4ch 5MP Lite@12fps; 4ch 4MP Lite/1080P@15fps; 1080P Lite@25fps, HDD: 1 Sata upto 10TB, Audio:1Ch; Upto 6CH IPC @2MP; 1 x HDMI & VGA; 1 x 10/100 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage; VQD; 2 x USB. | 5623.29 |
| 87 | HD DVR 4 Channel-5 | Channel: 4CH; Compression & MP: H.264/H.264+/H.265/H.265+ & 8MP@7fps,8MP lite@15fps,5MP@12fps,4MP@15fps,1080P/720P/960H/D1@25f ps(P)/30fps(N), HDD: 1 Sata upto 10TB, Audio:1Ch; Upto 6CH IPC @2MP; 1 x HDMI & VGA; 1 x 10/100 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage; VQD, 2 x USB. | 7247.80 |
| 88 | HD DVR 8 Channel-3 | Channel: 8CH; Compression & MP: H.264/H.264+ & 1MP/2MP : Resolution:8ch 1080P Lite@15fps; 960H1/D1/CIF real time, HDD: 1 Sata upto 8TB, Audio:1Ch; Upto 8CH IPC @2MP; 1 x HDMI & VGA; 1 x 10/100 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage; 2 x USB. | 4998.48 |
| 89 | HD DVR 8 Channel-4 | Channel: 8CH; Compression & MP: H.264/H.264+/H.265/H.265+ & 8ch 5MP Lite@12fps; 8ch 4MP Lite/1080P@15fps; 1080P Lite@25fps, HDD: 1 Sata upto 10TB, Audio:1Ch; Upto 10CH IPC @5MP; 1 x HDMI & VGA; 1 x 10/100 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage; VQD; 2 x USB. | 8185.01 |
| 90 | HD DVR 8 Channel-5 | Channel: 8CH; Compression & MP: H.264/H.264+ & 8MP@7fps,8MP lite@15fps, 5MP@12fps, 4MP@15fps,1080P/720P/960H/D1@25fps(P)/ 30fps(N), HDD: 1 Sata upto 8TB, Audio:1Ch; Upto 8CH IPC @8MP Lite; 1 x HDMI & VGA; 1 x 10/100 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage. | 13121.01 |

| | | | |
|----|------------------------------|--|----------|
| 91 | HD DVR 16 Channel (1 SATA)-1 | Channel: 16CH; Compression & MP: H.264/H.264+ & 16ch 1080P Lite@12fps; 960H1/D1/CIF real time, HDD: 1 Sata upto 8TB, Audio:1Ch; Upto 16CH IPC @2MP; 1 x HDMI & VGA; 1 x 10/100 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage. | 8431.19 |
| 92 | HD DVR 16 Channel (2 SATA)-1 | Channel: 16CH; Compression & MP: H.264/H.264+ & 16ch 1080P Lite@12fps; 960H1/D1/CIF real time, HDD: 2 Sata upto 8TB, Audio:1Ch; Upto 18CH IPC @2MP; 1 x HDMI & VGA; 1 x 10/100 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage. | 13440.91 |
| 93 | HD DVR 16 Channel (1 SATA)-2 | Channel: 16CH; Compression & MP: H.264/H.264+/H.265/H.265+ & 16ch 5MP Lite@12fps; 16ch 4MP Lite/1080P@15fps; 1080P Lite@25fps, 720P/960H/D1/CIF real time, HDD: 1 Sata upto 10TB, Audio:1Ch; Upto 20CH IPC @5MP; 1 x HDMI (4K Resolution) & VGA; 1 x 10/100/1000 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage; VQD; 2 x USB. | 12457.46 |
| 94 | HD DVR 16 Channel-2 | Channel: 16CH; Compression & MP: H.264/H.264+/H.265/H.265+ & 16ch 5MP Lite@12fps; 16ch 4MP Lite/1080P@15fps; 1080P Lite@25fps, 720P/960H/D1/CIF real time, HDD: 2 Sata upto 10TB, Audio:1Ch; Upto 20CH IPC @5MP; 1 x HDMI (4K Resolution) & VGA; 1 x 10/100/1000 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage; VQD; 2 x USB. | 18181.97 |
| 95 | HD DVR 16 Channel-2 | Channel: 16CH; Compression & MP: H.264/H.264+/H.265/H.265+ & 8MP@7fps,8MP lite@15fps,5MP@12fps,4MP@15fps,1080P/720P/960H/D1@25fps(P)/30fps(N), HDD: 2 Sata upto 10TB, Audio:1Ch; Upto 20CH IPC @8MP; 1 x HDMI(4K Resolution) & VGA; 1 x 10/100/1000 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage; VQD; 2 x USB. | 26991.79 |
| 96 | HD DVR 32 Channel-2 | Channel: 32CH; Compression & MP: H.264/H.264+/H.265/H.265+ & 32ch 5MP Lite@12fps/1080P@15fps/1080P Lite@25fps, HDD: 2 Sata upto 10TB, Audio:1Ch; Upto 20CH IPC @2MP & 5MP Lite; 1 x HDMI (4K Resolution) & VGA; 1 x 10/100/1000 RJ-45 Port; 3G/4G & Wi-Fi support; Cloud storage; VQD; 2 x USB. | 35314.26 |

| | | | |
|-----|-----------------|---|-----------|
| 97 | NVR 128 Channel | <p>Third-party network cameras supported</p> <ul style="list-style-type: none"> • Up to 12 Megapixels resolution recording • Video outputs at up to 4K (4096*2160) resolution • Supports decoding up to 20 channels at 1080P resolution • Up to 128/256 IP cameras can be connected with 512M/768M incoming bandwidth • Up to 24 SATA interfaces • Supports H.264+,H.264,MPEG4,H.265,MJPEG video format • Support redundant power supply to improve the system stability • Support HDD hot swap with RAID0,1,5,6,10 storage scheme configurable • Support various VCA detection alarm and VCA search | 656050.50 |
| 98 | NVR 32 Channel | <p>Maximum 320Mbps bitrate Input• 200Mbps bitrate input (RAID enabled)• Support 3rd party network cameras• Up to 12MP resolution recording• Support H.264/H.264+/H.265 video format• 2x HDMI & 2x VGA output (3840x2160)• Support RAID0, 1, 5, 10• Support redundant power supply• Dual digital network interfaces• 8x SATA, 1x eSATA, 2x USB2.0, 1x USB3.0• 19-inch rack-mounted 2U chassis, 4 Bay HDD, upto 128 Cam support</p> | 73602.62 |
| 99 | NVR 64 Channel | <p>Maximum 320Mbps bitrate Input• 200Mbps bitrate input (RAID enabled)• Support 3rd party network cameras• Up to 12MP resolution recording• Support H.264/H.264+/H.265 video format• 2x HDMI & 2x VGA output (3840x2160)• Support RAID0, 1, 5, 10• Support redundant power supply• Dual digital network interfaces• 8x SATA, 1x eSATA, 2x USB2.0, 1x USB3.0• 19-inch rack-mounted 2U chassis</p> | 133409.43 |
| 100 | 1 SATA-4ch | <p>Channels: 4ch.; Recording/transfer rate: 40Mbps; Prev/Playback:Up to 6 MP Resolution for Preview and Playback.</p> | 4936.00 |
| 101 | 1 SATA-8ch | <p>Channels: 8ch.; Recording/transfer rate: 40Mbps; Prev/Playback:Up to 6 MP Resolution for Preview and Playback.</p> | 6498.02 |
| 102 | 1 SATA-16ch | <p>Channels: 16ch.; Recording/transfer rate: 80 Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback.</p> | 8122.53 |

| | | | |
|-----|-----------------|--|----------|
| 103 | 2 SATA-4ch | Channels: 4ch.; Recording/transfer rate: 80 Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback. | 4936.00 |
| 104 | 2 SATA-8ch | Channels: 8ch.; Recording/transfer rate: 80 Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback. | 3498.94 |
| 105 | 2 SATA-16ch | Channels: 16ch.; Recording/transfer rate: 80 Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback. | 9718.29 |
| 106 | 2 SATA-8ch | Channels: 8ch.; Recording/transfer rate: 200Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback. | 5707.01 |
| 107 | 2 SATA-16ch | Channels: 16ch.; Recording/transfer rate: 200Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback. | 9718.29 |
| 108 | 2 SATA-32ch | Channels: 32ch.; Recording/transfer rate: 200Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback. | 16953.59 |
| 109 | 4 SATA-16ch | Channels: 16ch.; Recording/transfer rate: 200Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback. | 28116.45 |
| 110 | 4 SATA-32ch | Channels: 32ch.; Recording/transfer rate: 200Mbps; Prev/Playback:Up to 8 MP Resolution for Preview and Playback. | 33114.93 |
| 111 | 64 Ch. H.265 4K | Up to 64 channel IP camera input,Max 320Mbps incoming bandwidth,Smart H.265+/H.265/Smart H.264+/H.264/MJPEG,Up to 12Mp resolution preview and playback,Support 4 SATA HDDs up to 32TB, 3 USB Ports (2 Rear USB3.0,1 Front USB2.0),2 HDMI / VGA simultaneous video output,Support Multi-brand network cameras,ONVIF Version 2.4 conformance,Mobile Software: iCMOB, gCMOB,CMS Software: KVMS Pro | 50609.61 |
| 112 | 64CH NVR 8 SATA | Up to 64 channel IP camera input, Max 640Mbps Total bandwidth, Smart H.265+/H.265/Smart H.264+/H.264/MJPEG,Up to 12Mp resolution preview and playback, 8 SATA III Ports, up to 8TB capacity for each HDD, 4 USB(2 USB3.0, 2USB2.0), 2 HDMI / VGA simultaneous video output, Support Multi-brand network cameras, ONVIF Version 2.4 conformance, Support RAID 0/1/5/6/10, Mobile Software: iCMOB, gCMOB, CMS Software: KVMS Pro | 73727.58 |

| | | | |
|-----|--------------------------|---|-----------|
| 113 | Deepa-in-Mind Fusion NVR | <p>Powerful face pictures library management</p> <ul style="list-style-type: none"> • Face pictures comparison and alarm linkage actions • Search by picture supported • More precise face recognition and analytics based on deep learning algorithm • Up to 16-ch decoding at 1080p resolution • HDMI output at up to 4K resolution • Supports H.265+ decoding format • HDD hot swapping with RAID 0/1/5/6/10 | 67904.35 |
| 114 | NVR | <ul style="list-style-type: none"> • Third-party network cameras supported • Up to 12 Megapixels resolution recording • Video outputs at up to 4K (4096*2160) resolution • Supports decoding up to 20 channels at 1080P resolution • Up to 128/256 IP cameras can be connected with 512M/768M incoming bandwidth • Up to 24 SATA interfaces • Supports H.264+, H.264, MPEG4, H.265, MJPEG video format • Support redundant power supply to improve the system stability • Support HDD hot swap with RAID0,1,5,6,10 storage scheme configurable • Support various VCA detection alarm and VCA search | 558310.22 |
| 115 | 4CH POWER SUPPLY | <p>Input Voltage Range: 110VAC~300VAC; Metal Casing; DC Output, 5A, 12V; 4KV Surge protection; Over-Heat, Overload & Voltage Protection</p> | 749.77 |
| 116 | 8CH POWER SUPPLY | <p>Input Voltage Range: 110VAC~300VAC; Metal Casing; DC Output, 10A, 12V; 4KV Surge protection; Over-Heat, Overload & Voltage Protection</p> | 1124.66 |
| 117 | 16CH POWER SUPPLY | <p>Input Voltage Range: 110VAC~300VAC; Metal Casing; DC Output, 20A, 12V; 4KV Surge protection; Over-Heat, Overload & Voltage Protection</p> | 1749.47 |
| 118 | RACKS 2U | Wall Mount 350D with Front Glass Door Lock & Key 350 2U | 1874.43 |
| 119 | RACKS 4U | C Wallmount 400D With Front Glass Door Lock & Key 550 4U | 2249.32 |
| 120 | RACKS 6U | Wallmount 450D With Front Glass Door Lock & Key 550 6U | 4998.48 |

| | | | |
|-----|--------------------------------------|--|-----------|
| 121 | RACKS 9U | Wallmount 9U 630D With Front Glass Door Lock & Key 550 9U - (with 1U cable Manager;Fan;6 socket PDU) | 6872.91 |
| 122 | RACKS 42U | 42U Floor Standing Racks with Accessories | 52484.04 |
| 123 | Smart semi managed switches-24 | 24-Ports 10/100/1000Mbps + 4-Ports Combo GE/SFP Smart Managed Switch | 13884.53 |
| 124 | Smart semi managed switches-48 | 48-Ports 10/100/1000Mbps + 4-Ports Combo GE/SFP Smart Managed Switch | 30615.69 |
| 125 | L2 managed switches-8 | 8-Port 10/100/1000 Base-T + 2 Combo 10/100/1000BASE-T/SFP ports L2 Management Switch | 12496.20 |
| 126 | L2 managed switches-20 | 20-Port 10/100/1000 Base-T + 4 Combo 10/100/1000BASE-T/SFP ports + 2-Port 10G SFP+ L2 Management Switch | 43736.70 |
| 127 | L2 managed switches-24 | 24 SFP Ports + 4 SFP+ ports Managed Ethernet Switch | 43111.89 |
| 128 | L2 managed switches-48 | 48 Ports 10/100/1000Mbps + 4 10G ports SmartPro Switch | 93721.50 |
| 129 | L3 managed switches-20 | 20 10/100/1000Base-T ports + 4 Combo 10/100/1000Base-T/SFP ports + 4 10GE SFP+ ports L3 Stackable Managed Switch | 56232.90 |
| 130 | L3 managed switches-24 | 24x10G SFP+ & 2x40G QSFP ports L3 Managed switch | 225806.33 |
| 131 | L3 managed switches-2410 | 24 SFP ports + 2 10GBase-T ports + 4 10G SFP+ ports, L3 Stackable Managed Switch | 40612.65 |
| 132 | L3 managed switches-24 | 24 10/100/1000Base-T ports + 2 10GBase-T ports + 4 10G SFP+ ports, L3 Stackable Managed Switch | 40612.65 |
| 133 | L3 managed switches-48 | 48 10/100/1000Base-T ports + 2 10GBase-T ports + 4 10G SFP+ ports, L3 Stackable Managed Switch | 129335.67 |
| 134 | Smart semi-managed PoE switches-8 | 8-Ports 10/100/1000Mbps PoE + 2-Ports SFP 100/1000Mbp Smart Managed Switch, 65Watts | 11871.39 |
| 135 | Smart semi-managed PoE switches-8.1 | 8-Port 10/100/1000 Mbps + 2-Port SFP 1000 Mbps PoE switch | 12183.80 |
| 136 | Smart semi-managed PoE switches-24 | 24-Ports 10/100/1000Mbps PoE + 4-Ports Gigabit SFP Smart Managed Switch, 193Watts | 27291.70 |
| 137 | Smart semi-managed PoE switches-24.1 | 24-Port 10/100/1000 Mbps + 2-Port Combo 1000BASE-T/SFP PoE switch | 27291.70 |
| 138 | L2 managed PoE switches -24 | 24 Ports 10/100/1000Mbps PoE + 2 SFP ports + 2 10G ports SmartPro Switch | 36863.79 |
| 139 | L2 managed PoE switches -24.1 | 24 Ports 10/100/1000Mbps PoE + 4 10G ports SmartPro Switch | 37488.60 |
| 140 | L2 managed PoE switches - 48 | 48 PoE Ports 10/100/1000Mbps + 4 10G ports Smart Managed Switch | 121513.05 |
| 141 | L3 managed PoE switches-24.3 | 24 10/100/1000Base-T PoE ports + 2 10GBase-T ports + 4 10G SFP+ ports, L3 Stackable Managed Switch | 119963.52 |

| | | | |
|-----|------------------------------|--|-----------|
| 142 | L3 managed PoE switches-48.1 | 48 10/100/1000Base-T PoE ports + 2 10GBase-T ports + 4 10G SFP+ ports, L3 Stackable Managed Switch | 177133.64 |
| 143 | Long Distance Switches-4 | 4FE PoE + 2FE Uplink, 60 Watt PoE switch | 4373.67 |
| 144 | Long Distance Switches-8 | 8FE PoE + 1FE Uplink, 120 Watt PoE switch | 7435.24 |
| 145 | VMS for CCTV | all-in-one server that is composed of video management system (VMS), Operating System and hardware,Features include: user rights management,device management, alarm management, center storage,TV wall, 2-way audio talk, access control, video talk, entrance management, alarm controller and other advanced features | 312405.00 |
| 146 | 8 Channel SMPS | 12V 10 AMP SMPS / 12V 20 AMP SMPS | 1936.91 |
| 147 | Loaded Patch Pannel 24 Port | Loaded Patch Pannel 24 Port | 4061.27 |
| 148 | BNC Connectors | BNC (1.0 Vp-p, 75Ω), PAL / NTSC Self-adaptive | 62.48 |
| 149 | Camera DC Pin Connector | Camera DC Pin Connector | 43.74 |
| 150 | Video Signal cable (3 + 1) | RG 59 copper conductor for fixed cameras | 24.99 |
| 151 | LED Monitor 20 inch | 20" Screen size, 1920 X 1080 panel resolution, with USB, HDMI & Ethernet ports | 7372.76 |
| 152 | Display Units 32 inch LED TV | 32" Screen size, 1920 X 1080 panel resolution, with USB, HDMI & Ethernet ports | 27366.68 |
| 153 | Display Units 40"/43" LED TV | 40" / 43" Screen size, 1920 X 1080 panel resolution, with USB, HDMI & Ethernet ports | 39987.84 |
| 154 | Display Units 49"/50" LED TV | 49" / 50" Screen size, 1920 X 1080 panel resolution, with USB, HDMI | 46235.94 |
| 155 | Display Units 55" LED TV | 55" Screen size, 1920 X 1080 panel resolution, with USB, HDMI | 52484.04 |
| 156 | Viewing Computer System | Intel i3 Processor, 4GB Memory,1TB SATA HDD, Internal DVD Writer, 10/100/1000 Eth, Wireless Keyboard Mouse, 18.5" TFT Monitor, Win 8 Operating System | 61231.38 |
| 157 | Storage 2 TB SATA HDD | Compataible for installion on the DVR/NVR | 6248.10 |
| 158 | Storage 3 TB SATA HDD | Compataible for installion on the DVR/NVR | 8497.42 |
| 159 | Storage 4 TB SATA HDD | Compataible for installion on the DVR/NVR | 11871.39 |
| 160 | Storage 6 TB SATA HDD | Compataible for installion on the DVR/NVR | 15995.14 |
| 161 | Storage NAS 16 TB SATA HDD | 4 Bay Network Attached, Compataible for installion with the DVR's | 28741.26 |
| 162 | VGA Cable | VGA Cable of 20 Mts | 1624.51 |
| 163 | GI Pole with concrete | 3" 20Ft. G.I. Pole | 3279.00 |

| | | | |
|-----|---|---|----------|
| 164 | PVC Casing capping with installation per Meter | 25 mm Casing Capping | 74.98 |
| 165 | HDMI cable Dual ended 10 mtr | HDMI Cable of 10/20 Mts | 437.37 |
| 166 | HDMI cable Dual ended 20 mtr | HDMI Cable of 10/20 Mts | 599.82 |
| 167 | VGA cable 20 mtr | VGA Cable of 20 Mts | 349.89 |
| 168 | Storage NAS 16 TB SATA HDD | 4 Bay Network Attached, Compataible for installion with the DVR's | 43736.70 |
| 169 | PVC Casing capping with installation per Meter | 32 mm Casing Capping | 87.47 |
| 170 | CAT 6A UTP Cable (Per Mtrs) with laying and installation | 23 AWG solid bare copper, CAT-6A UTP Cable,Meets EIA/TIA 568-C.2 Category 6A specifications, CM Rated, Worst Case Cable Skew: 45 nsec/100 meters MAX. @ 250MHz maximum, Characteristic Impedence: 100±15%, 1-500 MHz, Insulation polyethylene, Conductor resistance 6.65ohm / 100m maximum, Solid Cable should be compliance to RoHS or FR PVC. Sheath Fire resistant OR LSZH, PAIRS Color code: Blue / White-Blue, Orange / White-Orange Green / White-Green, Brown / White – Brown, ELECTRICAL CHARACTERISTICS Input Impedance (250500 MHz): 100 +/- 25 Ohms Mutual Voltage 300 Volts AC or DC Capacitance: 5.6 nF/100 mtr. | 68.73 |
| 171 | SOLID CABLE CAT 6, 4 PAIR,UTP-per Mtrs with laying and installation | 4 pair, 100Ω, Unshielded twisted pair, Scanned till 500 MHz , Category 6gv specifications UL Listed Solid 4 pair 23 AWG Cat 6 Cable, Voltage: 30V, Dielectric Strength: 1000V AC, Current Rating: 1.5 Amps | 43.74 |
| 172 | Modular Switch Plate: 4M Module | ▪ Should be as per ISI certifications | 81.23 |
| 173 | Modular Switch Plate: 6M Module | ▪ Should be as per ISI certifications | 112.47 |
| 174 | Modular Surface Box: 4M Module | ▪ Should be as per ISI certifications | 74.98 |
| 175 | Modular Surface Box: 6M Module | ▪ Should be as per ISI certifications | 99.97 |
| 176 | Modular Electrical switches: 6 Amp | ▪ Should be as per ISI certifications | 62.48 |
| 177 | Modular Electrical switches: combination of 6 x 16 Amp | ▪ Should be as per ISI certifications | 131.21 |
| 178 | Modular Electrical Socket: 6 Amp | ▪ Should be as per ISI certifications | 124.96 |

| | | | |
|-----|---|---|----------|
| 179 | Modular Electrical socket: combination of 6 x 16 Amp | ▪ Should be as per ISI certifications | 231.18 |
| 180 | Electrical copper wire: 2.5, sq mm with insatallation per metre | ▪ Should be as per ISI certifications ▪ Should have CE certifications | 43.74 |
| 181 | 1kVA UPS with 30 minutes backup | Battery : Sealed Maintenance Free (SMF) batteries of 12V/14AH (7AHX2), Input Voltage : 160V to 280V AC, Single Phase, Input Frequency : 45 Hz to 55 Hz, Overload protection and Alarm | 3686.38 |
| 182 | 16 Channel SMPS | 12V 10 AMP SMPS / 12V 20 AMP SMPS | 2486.74 |
| 183 | 8-PORT 10/100/1000 MBPS UNMANAGED SWITCH | 1 K MAC Address 8x 10/100/1000 Mbps Ports Full Duplex, Auto MDI/MDI-X, IEEE 802.3, IEEE 802.3ab, IEEE 802.3x | 1499.54 |
| 184 | 8-PORT 10/100/ 1000 MBPS UNMANAGED POE SWITCH | 1 K MAC Address 8x 10/100/1000 Mbps Ports Full Duplex, Auto MDI/MDI-X, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x | 12483.70 |
| 185 | 16-PORT 10/100/ 1000 MBPS UNMANAGED SWITCH | 2 K MAC Address 16x 10/100/1000 Mbps Ports Full Duplex, Auto MDI/MDI-X, IEEE 802.3, IEEE 802.3ab, IEEE 802.3x | 6408.05 |
| 186 | 16-PORT 10/100/ 1000 MBPS UNMANAGED PoE SWITCH | 2 K MAC Address 16x 10/100/1000 Mbps Ports Full Duplex, Auto MDI/MDI-X, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x | 24992.40 |
| 187 | 24-PORT 10/100/ 1000 MBPS UNMANAGED SWITCH | 3 K MAC Address 24x 10/100/1000 Mbps Ports Full Duplex, Auto MDI/MDI-X, IEEE 802.3, IEEE 802.3ab, IEEE 802.3x | 8122.53 |
| 188 | 24-PORT 10/100/ 1000 MBPS UNMANAGED PoE SWITCH | 3 K MAC Address 24x 10/100/1000 Mbps Ports Full Duplex, Auto MDI/MDI-X, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x | 29019.93 |
| 189 | UTP to fiber transceiver 1 | 1. Up to 1.25Gb/s bi-directional data links 2. "Smart" Digital Diagnostics Functions 3. Extended Operating Temperature Range (0°C to +50°C) 4. Extended Power Supply Voltage (Operate at 3.3V and 5V) 5. Hot-Pluggable 6. Fully metallic enclosure for low EMI 7. Low power dissipation | 4207.47 |
| 190 | UTP to fiber transceiver 1 | 1. Up to 1.25Gb/s bi-directional data links 2. "Smart" Digital Diagnostics Functions 3. Extended Operating Temperature Range (0°C to +50°C) 4. Extended Power Supply Voltage (Operate at 3.3V and 5V) 5. Hot-Pluggable 6. Fully metallic enclosure for low EMI 7. Low power dissipation | 4748.56 |

| | | | |
|-----|--|--|----------|
| 191 | 1000 Base SX-transceivers with LC connector mm | 1. Hot-Pluggable 2. Low power dissipation | 4373.67 |
| 192 | 1000 Base SX-transceivers with LC connector sm | 1. Hot-Pluggable 2. Low power dissipation | 4373.67 |
| 193 | 1000 Base TX transceivers for copper | 1. Hot-Pluggable 2. Low power dissipation | 5623.29 |
| 194 | 10/100/1000 ethernet LAN extenders on Copper pair | 1 port RJ45 – 10/100/1000 Base-T - Shielded, Auto-MDIX enables proper operation with either straight-through or crossover cabling, Distance up to 100 meters (328 feet) as per IEEE 802.3, | 4373.67 |
| 195 | 10/100/1000 ethernet LAN extenders on optical fiber (SX) | 1 # Optical Fiber (1000 Mbps) with SC interface, 1 # RJ-45 (10/100/1000Mbps),Up to 120Km distance on single-mode fiber | 6872.91 |
| 196 | 19" 18U Wall Mount rack with necessary accessories | 18U/500MMD 1 SECN with front glass door lock, PDU 6x5Aamp and 1.5 meter feed cable and 3 pin plug, shelf 255m, Fan 203v 90 cfm, cable manager 1U pvc loops, Hardware pkt of 10, Load carrying capacity 40 kgs | 9996.96 |
| 197 | 19" 42 U Floor Mount rack with necessary accessories | 19" 42U floor mount rack with vented Front glass door with a fully vented rear steel door Fan Housing unit with 4 fans 230 V 90 CFM ,castors set of 4 with hardware packet (pack of 20), Equipment shelf 725 MMD, 1U PVC cable manager | 52484.04 |
| 198 | 1 Meter Dual Ended Mounting UTP Cat 6A patch Cord | 1 Meter Dual Ended Mounting UTP Cat 6A patch Cord | 93.72 |
| 199 | 2 Meter (s) Dual Ended Mounting UTP Cat 6A patch Cord | 2 Meter (s) Dual Ended Mounting UTP Cat 6A patch Cord | 187.44 |
| 200 | 3 Meter (s) Dual Ended Mounting UTP Cat 6A patch Cord | 3 Meter (s) Dual Ended Mounting UTP Cat 6A patch Cord | 281.16 |
| 201 | 5 Meter (s) Dual Ended Mounting UTP Cat 6A patch Cord | 5 Meter (s) Dual Ended Mounting UTP Cat 6A patch Cord | 462.36 |
| 202 | 10 Meter (s) Dual Ended Mounting UTP Cat 6A patch Cord | 10 Meter (s) Dual Ended Mounting UTP Cat 6A patch Cord | 749.77 |
| 203 | I/O Cat6A UTP Signal Port With Surface Mount Box | I/O Cat6A UTP Signal Port With Surface Mount Box | 527.34 |
| 204 | I/O Cat6A UTP Dual Port With Surface Mount Box | I/O Cat6A UTP Dual Port With Surface Mount Box | 687.29 |

| | | | |
|-----|---|---|---------|
| 205 | 24 Port, Cat 6A Jack Panel (Loaded with UTP I/O) | Type - 24-port, Unshielded Twisted Pair, Category 6, TIA / E1 Modular, PCB based and Keystone type Unshielded Twisted pair, category 6, EIA/TIA-568-C2 , The keystone modules are fire-retardant, moulded plastic modules UL94 VO rated, consisting of horizontal index strips for ease of retermination, 110 IDC Termination 180 degree Punch, allowing wires between 22 – 26 AWG sizes, Meets or Exceeds EIA/TIA –568–C.2 Category 6 connecting hardware specification, RJ45 (8P8C) T568A/T568B colour coding termination. Cable Guide way to guide the cable on the rear side, 1U size for 6/12/24 Ports and 2U for 48 Ports, UL Listed to “ANSI/TIA/ EIA-568-C2” specifications Jack Panel should be RoHS Complaint | 4373.67 |
| 206 | 1 Meter Dual Ended Mounting UTP Cat 6 patch Cord | 1 Meter Dual Ended Mounting UTP Cat 6 patch Cord | 187.44 |
| 207 | 2 Meter (s) Dual Ended Mounting UTP Cat 6 patch Cord | 2 Meter (s) Dual Ended Mounting UTP Cat 6 patch Cord | 262.42 |
| 208 | 3 Meter (s) Dual Ended Mounting UTP Cat 6 patch Cord | 3 Meter (s) Dual Ended Mounting UTP Cat 6 patch Cord | 343.65 |
| 209 | 5 Meter (s) Dual Ended Mounting UTP Cat 6 patch Cord | 5 Meter (s) Dual Ended Mounting UTP Cat 6 patch Cord | 437.37 |
| 210 | 10 Meter (s) Dual Ended Mounting UTP Cat 6 patch Cord | 10 Meter (s) Dual Ended Mounting UTP Cat 6 patch Cord | 687.29 |
| 211 | I/O Cat6 UTP Signal Port With Surface Mount Box | I/O Cat6 UTP Signal Port With Surface Mount Box | 374.89 |
| 212 | I/O Cat6 UTP Dual Port With Surface Mount Box | I/O Cat6 UTP Dual Port With Surface Mount Box | 562.33 |

| | | | |
|-----|---|---|---------|
| 213 | 24 Port, Cat 6 Jack Panel (Loaded with UTP I/O) | Type - 24-port, Unshielded Twisted Pair, Category 6, TIA / E1 Modular, PCB based and Keystone type Unshielded Twisted pair, category 6, EIA/TIA-568-C2 , The keystone modules are fire-retardant, moulded plastic modules UL94 VO rated, consisting of horizontal index strips for ease of retermination, 110 IDC Termination 180 degree Punch, allowing wires between 22 – 26 AWG sizes, Meets or Exceeds EIA/TIA –568–C.2 Category 6 connecting hardware specification, RJ45 (8P8C) T568A/T568B colour coding termination. Cable Guide way to guide the cable on the rear side, 1U size for 6/12/24 Ports and 2U for 48 Ports, UL Listed to “ANSI/TIA/ EIA-568-C2” specifications Jack Panel should be RoHS Complaint | 5623.29 |
| 214 | Electrical copper wire: 1 sq mm (1 Box- coil of 90 mts or higher) | ▪ Should be as per ISI certifications ▪ Should have CE certifications | 18.74 |
| 215 | Electrical copper wire: 4 sq mm (1 Box- coil of 90 mts) | ▪ Should be as per ISI certifications ▪ Should have CE certifications | 68.73 |
| 216 | Electrical copper wire: 6 sq mm (1 Box- coil of 90 mts) | ▪ Should be as per ISI certifications ▪ Should have CE certifications | 93.72 |
| 217 | Modular Electrical Socket: 6 Amp | ▪ Should be as per ISI certifications | 106.22 |
| 218 | Modular Electrical socket: combination of 6 x 16 Amp | ▪ Should be as per ISI certifications | 156.20 |
| 219 | Modular Surface Box: 2M Module | ▪ Should be as per ISI certifications | 56.23 |
| 220 | Modular Surface Box: 3M Module | ▪ Should be as per ISI certifications | 68.73 |
| 221 | Modular Surface Box: 8M Module | ▪ Should be as per ISI certifications | 137.46 |
| 222 | Modular Surface Box: 12M Module | ▪ Should be as per ISI certifications | 174.95 |
| 223 | Modular Switch Plate: 2M Module | ▪ Should be as per ISI certifications | 56.23 |
| 224 | Modular Switch Plate: 3M Module | ▪ Should be as per ISI certifications | 68.73 |
| 225 | Modular Switch Plate: 8M Module | ▪ Should be as per ISI certifications | 99.97 |
| 226 | Modular Switch Plate: 12M Module | ▪ Should be as per ISI certifications | 224.93 |
| 227 | MCB -63 Amp | ▪ Should be as per ISI certifications | 874.73 |
| 228 | MCB- 40 Amp | ▪ Should be as per ISI certifications | 624.81 |

| | | | |
|-----|---|--|----------|
| 229 | Earthing | Earthing with G.I earth pipe 2.5 Mtr. Long and 40 mm dia with salt and charcoal/coke as required. | 12483.70 |
| 230 | NA | | 0.00 |
| 231 | NA | | 0.00 |
| 232 | Installation for CCTV(Per Camera) | Camera Termination/Junction Box: Install, test and commission of the camera. The work shall include for all labour of camera fixing, camera stand fixing,DVR/NVR installation,Switch Insatallation, Patch Pannel Installation,Rack Installation Cable crimping with RJ 45 connector . All works related to End terminations and commissioning the camera on the network. | 624.81 |
| 233 | Installation with GI pole(Per Camera) | Gi Pole Fixing: The work shall include for all labour of Gi Pole fixing with cooncrete for installation of the camera. | 2374.28 |
| 234 | Service Engineer(per month) | Service Engineer: Deployment of service engineer for Full time onsite service & support for networking/CCTV per month | 22493.16 |
| 235 | CAT 6+ cable laying | Per Mtr | 24.99 |
| 236 | Input/Output Termination: | | 49.98 |
| 237 | Rack Fixing with all networking components. | | 999.70 |
| 238 | Electrical Termination Point (A) | | 187.44 |
| 239 | Electrical Termination Point (B) | | 374.89 |
| 240 | Electrical Wire Laying (A) | | 24.99 |
| 241 | Electrical Wire Laying (B) | | 37.49 |

Remark: NA stands for Not Applicable